

PRODUCT		V60	V6S	V80	V65	V85
QUANTITY	Pair/Single	Single	Single	Single	Single	Single
AUDIO	Driver Size - Woofer	6.5" x 1	6.5" x 1	8" x 1	6.5" x 1	8" x 1
	Driver Size - Mid range					
	Driver Size - Tweeter	0.75" Aimable x 1	0.75" Aimable x 2	0.75" Aimable x 1	1" Aimable x 1	1" Aimable x 1
	Driver Size - Base Radiator					
	Total Frequency response	33Hz - 27kHz	33Hz - 27kHz	30Hz - 27kHz	32Hz - 27kHz	30Hz - 27kHz
	Nominal Impedance	8 ohm	8 ohm	8 ohm	8 ohm	8 ohm
	Sensitivity	89dB	89dB	90dB	90dB	90dB
	Lower and Upper - 3db Limits	50Hz - 25 kHz	50Hz - 25 kHz	45Hz - 25 kHz	50Hz - 25 kHz	45Hz - 25 kHz
	Power (max)					
INPUTS	Audio Inputs					
	Speaker Inputs	1 Pair of push connectors - gold plated	1 Pair of push connectors - gold plated	1 Pair of push connectors - gold plated	1 Pair of push connectors - gold plated	1 Pair of push connectors - gold plated
EXTERNAL AMPLIFIER	Recommended amp power per channel	10 - 100 watts	10 - 100 watts Stereo 10 - 200 watts Surround	10 - 100 watts	10 - 125 watts	10 - 125 watts
ROOM ENVIRONMENT CONTROL	Room Switch					
	Wall Distance Switch					
	Imaging					
	Tweeter Switch					
	Enclosure type					
OVERALL	Mounting Type					
	Orientation				Vertical	Vertical
	Color	White grill	White grill	White grill	White grill	White grill
CUT-OUT SIZE	mm	208 Diameter	208 Diameter	238 Diameter	184 X 324	222 X 324
OVERALL SIZE	mm	245 Diameter	245 Diameter	283 Diameter	365 X 225	365 X 267
	Mounting Depth (includes 1/2" drywall)	82	82	92	73	79
	Mounting Height					
	Mounting Depth - Top Mount					
	Mounting Depth - Bottom Mount					
DIMENSIONS	(W x H x D) mm- each	245 Diameter x 95	245 diameter x 95	283 Diameter x 105	365 x 225 x 86	365 x 267 x 92
WEIGHT	kg	Shipping weight 1.81Kg	Shipping weight 5.44Kg	Shipping weight 2.27Kg	Shipping weight 2.27Kg	Shipping weight 2.72Kg